

Product specification

Product hierarchy / Date
 1730411 / 10.10.2017

General product information

Product hierarchy: 1730411
 Product description: SK 38/15 SIB 3T VENT (3420)
 One-piece screw cap with sealing conus and outer sealing lip, with slit tamper evidence band, with improved venting capacity, PE made, suitable to PET bottles with neck finish 38mm 3-start thread.
 Weight: 3,28 G +/-10%
 Customer drawing no.: ENG-01-008822

Customer drawing tolerances relate to the results of measurement averages, except for ovality. Ovality tolerances depend upon transport conditions, packaging media, vibration and temperature.

Neck material: PET
 Neck finish drawing no.: ENG-00-005024

Containers must meet BERICAP drawing specifications.

This closure should not be used for carbonated soft drinks or other filling goods, which can generate pressure by themselves in the bottle e.g. due to fermentation

Product properties

Components:	Resin HDPE General	Resin HDPE OrgLeptic	Resin Additive
Pack. unit:	1180X780X929 mm	575 X 375 X 392 mm	575X380X373 mm
Qty/pack. unit:	38.000	3.400	3.400
Pallet:	1200 X 800 mm	1000 X 1200 mm	1200 X 800 mm
Pack. units/pallet	1	25	20

Storage

Min. storage temperature: 10 °C
 Max. storage temperature: 35 °C

Pallets should be stored in a clean dry area away from UV light, smells and high temperature variations. Pallets should not be double stacked. Closures are to be used within 12 months after date of delivery.

The characteristics of the product are additionally fixed in separate process-, inspection- and sampling plans. Not subject to our automated up-date service.

Application

Min. application temperature:	18 °C
Max. application temperature:	28 °C
Manual application torque:	2,60 Nm (22,96 Inch lbs) +/-20%
Maximum head pressure/Topload:	200,0 N

Meeting the above requirements does not absolve the customer from the requirement to set up the capping equipment as required and from carrying out compatibility tests between the applied closure and filled product. Technical assistance can be provided by BERICAP.

The characteristics of the product are additionally fixed in separate process-, inspection- and sampling plans. Not subject to our automated up-date service.